

CYRUS

Thermostat Selection Chart



	CAL24	TC24	UC24	TS24	RT900	DT190	ET300	ET610	ET10	ET40	ET50	ET200	NT10	NT50	NT800	NT900	NC24
24 VAC supply	√	√	√	√	√	√											√
Line-voltage supply					√	√	√	√	√	√	√	√	√	√	√	√	√
Electro-mechanical					√	√											
Non-LCD	√				√	√	√	√									
LCD		√	√	√					√	√	√	√	√	√	√	√	√
Touch-screen				√						√						√	
Room Type	√	√		√	√		√	√	√	√	√	√	√	√	√	√	√
Duct Type / remote sensor	√	√	√	√		√	√	√	√	√	√	√	√	√	√	√	√
Line-voltage 3-speed output					√		√		√	√	√	√	√	√	√	√	
Separate power supply									√	√			√		√	√	
16 Amp 220 VAC output								√									
2-wire on-off output			√		√	√	√	√	√	√	√	√	√	√	√	√	√
3-wire floating output	√	√	√	√			√		√	√	√	√	√	√	√	√	√
0-10 VDC output	√	√	√	√			√		√	√	√	√	√	√	√	√	√
Modbus connection													√	√			√
BACnet MS/TP connection															√	√	